

PRODUCTS DESIGNED FOR THE ARCHITECTURAL MARKET

Special Purpose Applications

Product	Polymer NVM	pH	MFFT (°C)	Coalescing Solvent (on binder nvm)	Description
CONCRETE SEALERS, STAINS & PAINTS					
EPS 2257	40.0	8.0 - 9.0	7	4-5% Texanol	For Economical coatings, this all-acrylic emulsion offers excellent penetration, adhesion and water resistance..For use in clear sealers and stains.
EPS 2293	40.0	8.0 – 9.0	< 10	6 -10% Texanol	Designed for High Performance coatings. All-acrylic emulsion offering superior blush resistance and early wet adhesion. For use in clear sealers, stains and floor paints.

EPS low VOC technology is protected under U.S. patent number 6,762,230. Other patents are pending.

rev. 03/09/11

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option