



Urethane Resins for Wood Flooring & Clear Finishes

EXEMPT SOLVENT OIL MODIFIED URETHANES

PRODUCT	NVM	WPG	OIL TYPE	SOLVENT	ACID #	VISC	VISC. Reduced	COLOR	Sward Hardness	NOTES
EPS 4431	55.0%	9.63	Soya	PCBTF	2 Max.	Z ₂ -Z ₃	N/A	7 Max.	48	<ul style="list-style-type: none">• Fast dry, early hardness development• Exempt solvent, zero VOC• High gloss thru flat

Questions? Call EPS Technical Service @ 1-800-601-8111

rev 03-01-2011

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.