

HIGH-PERFORMANCE RESINS FOR ARCHITECTURAL COATINGS

Topcoats	EPS® 2706 Exterior					
	EPS® 2741 Interior/Exterior					
			EPS® 2799 Interior/Exterior			
Specialty	Concrete - Int/Ext Floor Paint		EPS® 2293 Sealer - Int/Ext Non-Blushing Clear Sealer			
	Concrete	EPS® 2559 Interior Waterproofers				
	Primer	EPS® 2533 Interior/Exterior				
	Coalescent	EPS® 9147 Interior/Exterior, Low VOC				
	Flat	Eggshell	Satin	Semi-Gloss	High Gloss	

Product	Chemistry	Solids (%)	pH Value	Weight per Gal (lb)	MFFT (°C)
EPS® 2799	All-Acrylic	48	8.5 - 9.0	8.85	21°
EPS® 2706	All-Acrylic	55	8.0 - 8.5	8.85	4°
EPS® 2741	All-Acrylic	50	8.5 - 9.0	8.80	10°
EPS® 2720	All-Acrylic	48	8.3 - 8.8	8.80	13°
EPS® 2533	Styrenated Acrylic	45.5	7.0 - 8.0	8.60	9°
EPS® 2293	All-Acrylic	40	8.0 - 9.0	8.70	< 10°
EPS® 2559	Styrenated Acrylic	50	7.0 - 8.0	8.70	44°

THE EXPERTISE BEHIND THE INNOVATION

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epasca.com/galleries/pdfs/salesterms.pdf>.

CONTACT INFORMATION

EPS Headquarters
1400 N. State St.
Marengo, Illinois 60152

Sales and Customer Service
Phone: 1-800-654-4242
Email: info@epasca.com

EPS Technical Service
Phone: 1-800-654-4242
Email: info@eps-materials.com

epasca.com