

# EPS<sup>®</sup> 2123

## STYRENE ACRYLIC EMULSION

# DATA SHEET

### Description

EPS 2123 is a styrene acrylic emulsion for use in removable pressure sensitive applications. EPS 2123 exhibits low peel, moderate tack, and high shear values.

- ✓ 180 Peel (PSTC-101) 2.4 lbs/inch
- ✓ Polyken Probe (ASTM D2979) 350 g/cm<sup>2</sup>
- ✓ Static Shear (PSTC-107) >10,000 minutes (1"x1"x1kg)

### Specifications

*Weight Solids:* 52.5 ± 1.5%

*Weight/Gallon:* 8.55 ± 0.10

*pH:* 7.0 - 9.0

### Typical Properties

*Volume Solids* 51.5 ± 1.5%

*Tg (measured):* -34°C

*Viscosity (#2 @20 rpm):* 600 - 1200 cps

*Acid Value (on solids):* N/A

062116

**Questions? Call EPS Technical Service @ 1-800-601-8111**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.