

EPS® 2570

Styrenated Acrylic Emulsion

MARKET SEGMENT: INDUSTRIAL METAL

COMMON APPLICATIONS: PRIMERS, TOPCOATS

EPS® 2570 is a self-crosslinking, styrenated acrylic emulsion offering excellent gloss, corrosion and chemical resistance, as well as early water resistance and rapid hardness development. EPS® 2570 provides the capability to formulate coatings at <100g/L VOC.

PERFORMANCE BENEFITS

- Hardness development
- Chemical resistance
- Block and mar resistance
- Corrosion resistance
- Adhesion to ferrous and non-ferrous metals
- Made without APEO surfactants

TYPICAL PROPERTIES

Weight Solids	48.0 +/- 0.7%
Weight/Gallon	8.60 +/- 0.1
pH	8.0 – 9.0
Volume Solids	46.0 +/- 0.7%
MFFT	42° C

These typical properties do not represent specifications.

SUGGESTED COALESCING SOVENT(S)

(% Solvent on Binder Solids – Pass 40°F LTC Test)

DPnB	10-15%
-------------	--------

SUGGESTED FORMULATIONS

- EPS® 2570 WHT SP-1 - White High Gloss Enamel
- EPS® 2570 WHT SP-2 - White High Gloss Enamel