

EPS® 2293

All-Acrylic Emulsion

MARKET SEGMENT: CONSTRUCTION, INDUSTRIAL, ARCHITECTURAL

COMMON APPLICATIONS: TOPCOAT, SEALER

EPS® 2293 is a self-crosslinking all-acrylic emulsion offering excellent adhesion and early water resistance for use in clear sealers over tiles and cementitious substrates. Clear and pigmented coatings can be formulated at less than 100 g/l VOC. EPS® 2293 offers excellent performance in exterior stain formulations for deck and wood applications and garage floor paint.

FORMULA: EPS® 2293 CS2 (6/15/2009) - Clear Wet-Look Sealer/Stain Base for Concrete

Pounds	Gallons	Raw Material	Supplier	Instructions
183.3	22.00	Water		Add raw materials under good agitation.
645.3	73.75	EPS® 2293	EPS	
3.0	0.34	Surfynol PSA-336	Evonik	
3.0	0.35	BYK 024	BYK	
15.0	1.89	Texanol	Eastman	
3.0	0.40	Ammonium Hydroxide 28%		
5.0	0.56	Proxel AQ	Lonza	Use to rinse mill.
<u>9.3</u>	<u>1.00</u>	Ethylene Glycol		
866.9	100.29	Totals		

Formulation Properties	
Weight Solids	30.45%
Volume Solids	27.83%
Pigment Weight	
Pigment Volume Conc.	0%
VOC Level	
	98 g/L
Weight/Gallon	
	8.64 lb/gal

Typical Properties	
Viscosity	12-18 sec
pH	8.5-9.5
Color	Clear
Suggested Application Methods:	
Brush, Roller, Spray	

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

7/30/2024

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epsgca.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epsgca.com/galleries/pdfs/salesterms.pdf>.