

EPS® 2460

All-Acrylic Emulsion

MARKET SEGMENT: INDUSTRIAL WOOD

COMMON APPLICATIONS: TOPCOAT

EPS® 2460 is an all-acrylic, film-forming polymer for flat through semi-gloss interior and exterior architectural and industrial wood coatings with exceptional adhesion, block resistance, chemical resistance and hardness development. Designed for OEM applications, EPS® 2460 is ideal for pigmented coatings for shutters, windows, doors and joinery. It is also recommended for interior applications such as kitchen and bathroom cabinets.

PERFORMANCE BENEFITS

- Adhesion
- Exterior durability
- Block resistance
- Chemical resistance
- Hardness development
- Flow and leveling
- Formulated without the use of intentionally added fluorosurfactants
- Made without APEO surfactants

TYPICAL PROPERTIES

Weight Solids	48.0 ± 0.7%
Weight/Gallon	8.75 ± 0.10
pH	7.8 – 8.8
Volume Solids	47.2 ± 0.7%
MFFT	5° C
Volatile(s)	Water, ammonia

These typical properties do not represent specifications.

SUGGESTED FORMULATIONS

- EPS® 2460 Flat White Pigmented Topcoat
- EPS® 2460 Semi-Gloss White Topcoat