



## HIGH-PERFORMANCE ADHESIVES AND SEALANTS

	<b>EPS® 2157</b> Moderate peel and tack, high shear				
	<b>EPS® 2156D</b> Low peel, moderate tack, high shear				
<b>EPS® 2133</b> Moderate peel, high tack, high shear					
<b>EPS® 2127D</b>		<b>EPS® 2127D</b> High peel, high tack, moderate shear, low foaming			<b>EPS® 2127D</b>
	<b>EPS® 2123D</b> Low peel, moderate tack, high shear, low foaming				
	<b>EPS® 2121</b> Low peel, high shear				
<b>Permanent PSAs</b>	<b>Removable PSAs</b>	<b>Tape and Labels</b>	<b>Protective Masking</b>	<b>Vinyl Flooring Adhesive</b>	<b>Caulks and Sealants</b>

Product	Chemistry	Solids (%)	pH	Tg (°C)
EPS® 2121	All-Acrylic	50.0	7.0-8.0	-32
EPS® 2123D	Styrenated Acrylic	52.0	7.0-9.0	-34
EPS® 2127D	All-Acrylic	60.0	8.0-9.0	-45
EPS® 2156D	All-Acrylic	55.0	7.0-9.0	-41
EPS® 2157	All-Acrylic	52.0	6.0-8.0	-40
EPS® 2133	All-Acrylic	57.0	7.0-8.0	-34

### THE EXPERTISE BEHIND THE INNOVATION

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at [www.epscca.com/galleries/pdfs/salesterms.pdf](http://www.epscca.com/galleries/pdfs/salesterms.pdf).

### CONTACT INFORMATION

EPS Headquarters  
1400 N. State St.  
Marengo, Illinois 60152

Sales and Customer Service  
Phone: 800-654-4242  
Email: [info@epscca.com](mailto:info@epscca.com)

EPS Technical Service  
Phone: 800-654-4242  
Email: [info@eps-materials.com](mailto:info@eps-materials.com)

[epscca.com](http://epscca.com)