

# EPS® 2210D

## All-Acrylic Emulsion

**MARKET SEGMENT: CONSTRUCTION**

**COMMON APPLICATIONS: TOPCOAT**

EPS® 2210D is an acrylic emulsion designed for use in elastomeric roof and wall coatings. Coatings formulated with EPS® 2210D are capable of conforming to ASTM D6083 Type II standards while still providing excellent asphalt bleed-through and dirt pickup resistance.

### PERFORMANCE BENEFITS

- Weatherability
- Dirt Pickup Resistance (DPUR)
- Adhesion to most roofing substrates
- Excellent balance of tensile and elongation properties
- Low foaming

### TYPICAL PROPERTIES

Weight Solids	55.0 +/- 0.7%
Weight/Gallon	8.70 +/- 0.10
pH	7.5-8.5
Volume Solids	53.0 +/- 0.7%
Tg	-12° C
Volatile(s)	Water

### SUGGESTED COALESCING SOVENT(S)

(% Solvent on Binder Solids – Pass 40°F LTC Test)

EPS® 9147	<2.5%
-----------	-------

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: [info@eps-materials.com](mailto:info@eps-materials.com)

9/16/2025

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at [www.epscsa.com](http://www.epscsa.com).

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epscsa.com/galleries/pdfs/salesterms.pdf>.