

## RayFlex® 765

### Styrenated Acrylic Emulsion

**MARKET SEGMENT: CONSTRUCTION**

**COMMON APPLICATIONS: TOPCOAT**

RayFlex® 765 is a styrenated acrylic elastomer designed for a wide variety of exterior coatings. It is ideal for flexible roof coatings, textured finishes, and wall mastics. Coatings formulated with RayFlex® 765 offer excellent tensile strength, elongation properties, low-temperature flexibility and outstanding water resistance.

#### PERFORMANCE BENEFITS

- Elongation and strength
- Water resistance
- Vapor permeability
- Low-temperature flexibility
- Shear stability
- Reactive pigment compatibility
- Made without APEO surfactants

#### TYPICAL PROPERTIES

<b>Weight Solids</b>	50%
<b>Weight/Gallon</b>	8.60
<b>pH</b>	7.0 – 8.0
<b>Volume Solids</b>	48.4%
<b>MFFT</b>	<0°C
<b>Volatile(s)</b>	Water

#### SUGGESTED COALESCING SOVENT(S)

**(% Solvent on Binder Solids – Pass 40°F LTC Test)**

<b>Texanol</b>	3% - 5%
----------------	---------

#### SUGGESTED FORMULATIONS

- Elastomeric Roof Coating <100 g/L VOC